



19"-Rack Cabinet 6+2RU

The 6+2RU rack Cabinet is used for the housing of active or passive equipment, visible from the outside and protected by a safe steel lockable structure. Compatible with optical fiber, data cables or coaxial cable installations, it allows the grouping of different technologies in a single cabinet. Total capacity is 8RU, namely 6RU and an additional 2RU, taking advantage of the top and bottom ends. Designed for either wall or ground mounting.

Dimensions (W x H x D): 600mm x 370mm x 450mm

Weight: 22.5kg

Ref. 533105

Logical ref. MSR196B

EAN13 8424450210338

Other features

Supply method Disassembled

Rack depth 450mm

Height (RU) 6+2RU

Perforated doors

Packing

Box 1 pcs.

Highlights

Physical data

Net weight 20,750.00 g

Gross weight 22,500.00 g

Width 600.00 mm

Height 370.00 mm

Depth 450.00 mm

Main product weight 20,750.00 g

- High strength and durability: made of steel, with a coating based on polyester resins and lead-free pigments
- Loading capacity up to 60kg
- Easy to mount: includes an L-bracket for wall mounting
- Bracket independent of the rack: allows to mark the drilling points on the wall, screw it in and then hang the rack on it
- Practicality of use: reversible and removable front door with flexible sockets and hinged folding side doors
- Installation of different types of panels or equipment: lateral profiles are depth-adjustable
- Safety: Tempered glass, lockable hinged front door
- Natural ventilation, with forced ventilation option
- Laser marking: numerical identification of each "RU"

Main features

- Black colour (RAL 9004)
- Horizontal cable guides: 1U cable panels located at the top and bottom of the cabinet to lead cabling from one side to the other and facilitate connections
- Indoor installation (IP20)
- A 120x120mm ventilation kit can be incorporated for the installation of active equipment, such as headends

Discover

Compatibility of our racks with wheels:

Depth	Height	Ref.	Mounting	Compatible with wheels
450mm	6RU	533105 533106	Wall or floor	x
	8RU	533107 533108		
	13RU	533112 533113		
	15RU	533114 533115		
600mm	15RU	533116		
600, 800 and 1000mm	18RU	533118	Floor	OK
	22RU	533122		
	27RU	533127		
	32RU	533132 533134		
	37RU	533137 533139		
	42RU	533142 533144 533145 533146 533147		

Recommended ventilation systems for racks:

All our racks are equipped with natural ventilation, but in most cases this is not sufficient as high temperatures can affect the performance of the individual parts of the connection. We therefore recommend installing a **forced ventilation system**.

Our fans are for ceiling installation because they take advantage of the natural upward flow of warm air by placing them at the top of the enclosure.

The compatibility between our racks and fans is described below.

Depth	Height	Ref	Fan

Depth	Height	Ref	Fan
450mm	6U	533105 533106	533174
	8U	533107 533108	
	13U	533112 533113	
	15U	533114 533115	
		533116	
600mm	18U	533118	533175
	22U	533122	
	27U	533127	
	32U	533132	
	37U	533137 533139	
	32U	533134	
800mm	37U	533139	533176
	42U	533142	
		533144 533145	
1000mm	42U	533146 533147	

Technical specifications : Ref. 533105

Modular spacing (standard)	in	19
Height	mm	370
Width	mm	600
Depth	mm	450
Number of rack units (HE)		6
Rack material		Steel
Colour		Black
Surface finishing		Electrostatic powder
Number of doors		1
Rear door		No
Max. load capacity	kg	60
Removable sides		Yes
Installation type		Wall / Ground
Type of profile rail		L-shaped
Grounding		No